



WIRING TABLE

P1		P2	
RESERVED	A1	B1	RESERVED
GND	A2	B2	GND
Rx0+	A3	B3	Tx0+
Rx0-	A4	B4	Tx0-
GND	A5	B5	GND
Rx1+	A6	B6	Tx1+
Rx1-	A7	B7	Tx1-
GND	A8	B8	GND
SB	A9	B9	SB
SB	A10	B10	SB
GND	A11	B11	GND
SB	A12	B12	SB
SB	A13	B13	SB
GND	A14	B14	GND
Rx2+	A15	B15	Tx2+
Rx2-	A16	B16	Tx2-
GND	A17	B17	GND
Rx3+	A18	B18	Tx3+
Rx3-	A19	B19	Tx3-
GND	A20	B20	GND
RESERVED	A21	B21	RESERVED
RESERVED	B1	A1	RESERVED
GND	B2	A2	GND
Tx0+	B3	A3	Rx0+
Tx0-	B4	A4	Rx0-
GND	B5	A5	GND
Tx1+	B6	A6	Rx1+
Tx1-	B7	A7	Rx1-
GND	B8	A8	GND
SB	B9	A9	SB
SB	B10	A10	SB
GND	B11	A11	GND
SB	B12	A12	SB
SB	B13	A13	SB
GND	B14	A14	GND
Tx2+	B15	A15	Rx2+
Tx2-	B16	A16	Rx2-
GND	B17	A17	GND
Tx3+	B18	A18	Rx3+
Tx3-	B19	A19	Rx3-
GND	B20	A20	GND
RESERVED	B21	A21	RESERVED

NOTE:  
 1.100%OPEN&SHORT TESTIGN,  
 2.INSULATION RESISTANCE 10M Ohm MIN DC300V  
 3.CONDUCTIVE RESISTANCE: 2 Ohm MAX

NO.	PART NAME	PART NO.	SPEC DESCRIPTION	QTY	UNIT
9	EXPANDD	AQ-3-MS76001	PET BALCK OD: 10mm	A/R	mm
8	MOLDING	AQ-3-GL10101	LDPE NATURAL	A/R	g
7	ACETATE TAPE	AQ-3-MS77001	W=25±5mm	A/R	mm
6	CONN	AQ-3-MS51C02	OCULINK 4I CONN PIN: Au 15u	1	PCS
5	PCB	AQ-3-MS31022	OCULINK 4I PCB 88±8 ohm	1	PCS
4	HOOK	AQ-3-MS64002	OCULINK 4I HOOK_UP PC+ABS, BLACK	2	PCS
3	HOOK	AQ-3-MS64001	OCULINK 4I HOOK_DOWN PC+ABS, BLACK	2	PCS
2	CABLE	AQ-3-MS20101	30AWG CABLE	A/R	mm
1	CABLE	AQ-3-MS40207	(32AWG*2C+2D)AL+MYLAR,OD:0.65*1.54MM,85±5 ohm.	A/R	mm

A	INITIAL RELEASE		20/06/27
REV	DESCRIPTION OF CHANGE		DATE
TOLERANCE		DIKWAN® DONGGUAN AIQUN INDUSTRIAL CO., LTD.	
INCHES	M/M		
.X	.015 .30		
.XX	.010 .10		
.XXX	.005 .05	SCALE	NONE
DRAWN BY	TONY CHAN	UNIT	MM
		SHEET	1/1
CHECK BY		DATE	22/06/27
		TITLE	OCULINK 4i TO 4i
CUSTOMFR P/N		P/N: AQ-1-MS881010500	