



NOTE:
 1.100%OPEN&SHORT TESTIGN,
 2.INSULATION RESISTANCE 10M Ohm MIN DC300V
 3.CONDUCTIVE RESISTANCE: 2 Ohm MAX

NO.	PART NAME	PART NO.	SPEC DESCRIPTION	QTY	UNIT
13	LATCH	AQ-3-MS21008	STAINLESS STEEL	2	pcs
12	MOLDING	AQ-3-GL100101	LDPE,NATURAL	A/R	g
11	MOLDING	AQ-3-GL100401	PBT+30GF% BLACK	A/R	g
10	PCBA	AQ-3-MS31019	MINI SAS 36PIN PCB, PIN:15u Au, 105±10 ohm	2	PCS
9	EXPANDO	AQ-3-MS76001	PET BALCK DD: 10mm	A/R	mm
8	MOLDING	AQ-3-GL10501	PA BLACK	A/R	g
7	ACETATE TAPE	AQ-3-MS77001	W=25±5mm	A/R	mm
6	PCB	AQ-3-MS31023	MINI SAS HD 4I PCB(A/B),PIN: AU 15u&30u,100±10 ohm	1	PCS
5	PCB	AQ-3-MS31022	MINI SAS HD 4I PCB(C/D),PIN: AU 15u&30u,100±10 ohm	1	PCS
4	COVER	AQ-3-MS64002	MINI SAS HD 4I PC BLACK	1	PCS
3	HOUSING	AQ-3-MS64001	MINI SAS HD 4I PC BLACK	1	PCS
2	CABLE	AQ-3-MS20101	30AWG CABLE	A/R	mm
1	CABLE	AQ-3-MS40206	<30AWG*2C+2d>*Al+MYLAR,DD:0.97*2.17MM,100±10 ohm	A/R	mm

REV	DESCRIPTION OF CHANGE	DATE
A	INITIAL RELEASE	12/10/12
TOLERANCE		
INCHES MM		
.X	.015 .30	DIKWAN [®] DONGGUAN AIQUN INDUSTRIAL CO., LTD.
.XX	.010 .10	
.XXX	.005 .05	
DRAWN BY	TONY CHAN	SCALE: NONE
CHECK BY		UNIT: MM
CUSTOMER P/N:	P/N: AQ-1-MS311S10500	SHEET: 1/1
		DATE: 16/04/10
		DWG NO:
		TITLE: MINI SAS HD 4I TO 36P SE