



ELECTRICAL CHARACTER:

- a. 100% OPEN&SHORT TESTING;
- b. WITHSTANDING VOLTAGE:DC 300V 0.01Sec;
- c. INSULATION RESISTANCE:10M Ohm(Min);
- d. CONDUCTIVE RESISTANCE:2 Ohm(Max).

NO.	PART NAME	PART NO	SPEC DESCRIPTION	QT'Y	UNIT	CUSTOMER. P/N:	P/N: AQ-1-MS411012000
8	LATCH	AQ-3-MS21008	STAINLESS STEEL	1	PCS		
7	ACETATE TAPE	AQ-3-MS77001	W=25±5mm, BLACK	A/R	mm		
6	MOLDING	AQ-3-GL100401	PBT+30GF% BLACK	A/R	KG		
5	PCBA	AQ-3-MS31019	MINI SAS 36PIN PCB, PIN:15u' Au, 105±10 ohm	1	PCS		
4	MOLDING	AQ-3-GL100101	LDPE RDHS	A/R	KG		
3	ASSEMBLY PARTS	AQ-3-MS62001	MINISAS 26P ASSEMBLY <Zinc ALLOY HOODS, HOOD,PULL-TAB, RUBBER RING>	1	set		
2	PCBA	AQ-3-MS31021	MINISAS 26P PCBA, PIN:15u Au, 100±10 Ohm	1	PCS		
1	CABLE	AQ-3-MS41603	<30AWG*2C+D+HMAM+HM>*8C+M+AM+B,OD:6.8MM, BLACK PVC JACKET 100±5 Ohm	A/R	mm		

REV	DESCRIPTION OF CHANGE	DATE
A	INITIAL RELEASE	13/03/02

TOLERANCE INCHES	M/M
.X	.015 .30
.XX	.010 .10
.XXX	.005 .05

SCALE	NONE	REV	A
UNIT	MM		
SHEET	1/3	CUSTOMER:	
DATE	15/03/02	DWG NO.:AQ13-021	
TITLE: MINI SAS HD 4x TO MINISAS 36P			

DRAWN BY	TONY CHAN
CHECK BY	